

NOTES:

- 1. SEE THE APPROVED MATERIAL LIST FOR METER BOX SCHEDULE
- 2. H20 TRAFFIC LOAD RATED BOXES & LIDS TO BE USED IN TRAFFIC AREAS.
- 3. ALL METER BOXES MUST BE SET TRUE, PERPENDICULAR TO STREET, AND FLUSH WITH SIDEWALK.
- 4. SPACE BETWEEN BOXES IN MULTIPLE METER INSTALLATIONS SHALL BE 2".
- 5. DO NOT SET METER BOXES ON PRIVATE PROPERTY.
- 6. LID TO BE ONE PIECE, MARKED WATER, AND TOUCH-READ READY WITH 2" PROBE HOLE.
- 7. IN SLOPED AREA METER BOX MAY REQUIRE REDWOOD RETAINING WALLS.
- 8. METER BOXES AND LIDS IN TRAFFIC AREAS SHALL BE H-20 TRAFFIC RATED. INSTALL 6" CONCRETE COLLAR (6" DEEP) AROUND TRAFFIC-RATED METER BOXES.
- METER BOXES OUTSIDE OF TRAFFIC AREAS AND NOT IN SIDEWALK SHALL HAVE 6" WIDE COLLAR (4" DEEP).
- 10. RECYCLED WATER METER BOX INSTALLATION SHALL BE IDENTIFIED AS RECYCLED WATER FACILITIES PER SECTION IV-B1-2.04.

Dublin San Ramon Services District	REVISION DATE NOV 2019
METER BOX INSTALLATIONS 5/8 INCH TO 2 INCH	REVISED BY KP
SIGNED COPY ON FILE AT DISTRICT OFFICE	DRAWING W-19